



| La cardeuse la plus performante du marché

| The most powerful carding machine on the market

**SOUFFLAGE / INSUFFLATION
TOUS PRODUITS ISOLANTS EN
FLOCONS**

**BLOWING / INSUFFLATION
ALL INSULATING PRODUCTS
IN FLAKES**



Caractéristiques techniques

| | |
|----------------------------|---|
| Puissance air | 3 moteurs (4.50kw) 300 mb de pression |
| Dimensions (m) | 1,25x0.86x1.58 |
| Poids | 320 kg |
| Diamètre tuyau | Ø 100 mm |
| Longueur tuyau maxi | 80 m |
| Débit de soufflage | Jusqu'à 1800 kg/h en fonction du produit (+ de 300m ² /h en R7 |
| Alimentation | 2x230 V monophasé – 16A (possibilité en 400 V |
| Insufflation | Arrêt automatique par pressostat |

Technical characteristics

| | |
|----------------------------|---|
| Air power | 3 motors (2.50kw) 300 mb of pressure |
| Dimensions (m) | 1,25x0.86x1.58 |
| Weight | 320 kg |
| Hose diameter | Ø 100 mm |
| Maximum hose length | 80 m |
| Product flow | Depending on product up to 1800 kg/h (more than 300m ² /h in R7) |
| Power supply | 2x230 V single-phase – 16 A (possibility in 400 V) |
| Injection | Automatic stop by pressostat |

**Décompactage automatique par système
breveté de défibrage par brosses rigides
Brevet N°FR1914825**

**Automatic decompaction by means of a patented
system of defibration by rigid brushes
Patented N°FR1914825**

